

550-650 W High Wattage Fan Heater scr Series







Features

- For large heating capacity requirements.
- Maintains minimum operating temperatures in enclosures.
- Helps prevent failures to components caused by condensation and corrosion.
- Built-in thermostat and control light.
- Heating power adjusts to ambient temperature.
- Heat exits top of fan heater. (add 2" clearance for heat sensitive parts)

		Inrush		Temperature	Ship Wt.
Part No.	Watts	Current (Amps)	Volts	Maximum with Fan	lbs
SCR027009	550 W	14 A	AC 120	250°F/120°C	2
SCR027009230	550 W	13 A	AC 230	250°F/120°C	2
SCR027019	650 W	15 A	AC 120	320°F/160°C	2.4

Air Flow:	20 CFM (550W), 26 CFM (650W)		
Thermostat Range:	32 - 140 degrees Fahrenheit		
Heating Element:	PTC - Semiconductor/resistor		
Housing:	Plastic, rated UL94-VO		
Connection:	3 pole terminal, AWG 14 max (2.5 mm2)		
Mounting:	Clip for 35mm DIN rail		
Protection Class:	II (Double Insulated)		
Protection Type:	IP20		
Approval:	UL Recognized Component, cUL Recognized Component, CE		

Data subject to change without notice