



FEATURES:

- Industry standard double banana plug adapts to any meter with input jacks at 3/4" spacing
- Link several pieces of test equipment to the same input using stacking connectors in the double plug
- 48 inch length of cable is shielded to protect against electrical noise
- 1 foot leads are Silicone insulated for maximum heat resistance
- Shielded cable is stiff enough to ensure proper placement engine compartment minimizing risk of tangling with moving belts and pulleys
- Industry standard shrouded plugs attach to test probes, alligator clips and other clips
- Black plug is connected to the "GND" side of the double plug

MATERIALS:

Double Banana Plug:

Spring: Nickel-plated Beryllium Copper

Body: Nickel-plated brass

Insulator: Polypropylene, black

Cable: RG 58C/U

Breakouts:

Spring: Nickel-plated Beryllium Copper

Body: Nickel-plated Brass

Insulators: Thermoplastic elastomer, red and black

Leads: 20 AWG Silicone, gray

RATINGS:

Operating Voltage: For use in controlled voltage environments: Non hand-held use: 300 VRMS
For probing or hand-held use: 60 VDC Max.

Current: 5 Amperes

ORDERING INFORMATION: Model 6480

All dimensions are in inches.

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA