

RF 1:1 Transmission Line Transformer 4.5-3000 MHz

Rev. V5


Features

- Surface mount
- Wide frequency range
- 1:1 impedance
- Lead Free
- RoHS* Compliant and is 260°C reflow compatible.
- Available on Tape and Reel, reel quantity 2000

Description

M/A-COM's MABA-010125-TC1113 is a RoHS compliant 1:1 RF transmission line transformer in a low cost, surface mount package. The windings of the MABA-010125-TC1113 are welded to the package substrate for improved reliability and to eliminate lead content. Ideally suited for high volume cellular and wireless application. Parts are packaged in tape & reel.

Schematic




Product Image




Pin Configuration

Pin No.	Function	
1	Secondary Dot	
2	Not Connected	
3	Secondary	
4	Primary	
5	Primary Dot	

Case-style Dimensions





Dimensions are inches (millimeters) ±0.015 (0.38) unless otherwise specified.

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.

PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

- North America Tel: 800.366.2266 Europe Tel: +353.21.244.6400
- India Tel: +91.80.43537383
- China Tel: +86.21.2407.1588 Visit www macomtech com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.

^{*} Restrictions on Hazardous Substances, European Union Directive 2002/95/EC.



RF 1:1 Transmission Line Transformer 4.5-3000 MHz

Rev. V5

Electrical Specifications: $T_A = 25 \,^{\circ}\text{C}$, $Z_0 = 50 \,^{\circ}\text{C}$

Parameter	Test Conditions	Test Conditions	Units	Min	Тур	Max
RF Frequency	-	4.5 - 3000	MHz	-	-	-
Insertion Loss	-	4.5 - 1000 1000 - 2000 2000 - 3000	dB dB dB	- - -	0.3 1.5 2.8	1.0 2.0
Amplitude Unbalance	-	4.5 - 3000	dB	-	0.5	1.0
Phase Unbalance	-	4.5 - 3000	Degrees	-	5	20

Absolute Maximum Ratings ^{1,2}

Parameter	Absolute Maximum
DC Power	250 mW
DC Current	50 mA
Operating Temperature	-40℃ to +85℃
Storage Temperature	-55℃ to +125℃

Exceeding any one or combination of these limits may cause permanent damage to this device.

M/A-COM does not recommend sustained operation near these survivability limits.




RF 1:1 Transmission Line Transformer 4.5-3000 MHz


Rev. V5

Typical Performance Curves


Insertion Loss




Amplitude Unbalance



Phase Unbalance



Input Return Loss




- India Tel: +91.80.43537383
 - China Tel: +86.21.2407.1588 Visit www.macomtech.com for additional data sheets and product information.



RF 1:1 Transmission Line Transformer 4.5-3000 MHz

Rev. V5

Tape & Reel Information



Item	Dimension
Ao	4.00mm +/-0.1mm
Во	4.00mm +/-0.1mm
Ko	2.9mm +/-0.1mm
W	12.00mm +/-0.3mm
P1	8.00mm +/-0.1mm

Ordering Information

Part Number	Package
MABA-010125-TC1113	Tape and Reel (2000 piece Reel)

is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.

PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

India Tel: +91.80.43537383
 China Tel: +86.21.2407.1588
 Visit www.macomtech.com for additional data sheets and product information.