




2. Material and Finish:

- Receptacle Housing (with Flange): Zinc Die-Cast,

- Finish: Powercron 150 (PPG), Black - Panel Gasket: NBR, Color: Black
- M3 Mounting Hardware: Stainless Steel Includes 4 x (Screw + Nut + Flat Washer + Spring Lock Washer)
- USB Adaptor Insulator: PBT, UL94 V-0, Black
- USB Adaptor Metal Shell: Copper Alloy, Nickel Plated
- USB Adaptor Overmold material: PBT UL94 V-0, Color: Black
- USB Contacts: Copper Alloy, Finish: 30 u" Gold min. over Nickel
- 3. Connector can be front or rear mounted to a maximum panel thickness of 3.2 mm.
- 4. IP67 rated when fully mated with appropriate mating connector
- 5. Hardware shipped unassembled
- (b) 6. Recommended mounting torque is 8 to 10 lb-inch







Pin-Assignment

	3
Type A	Type A
Female	Female
Pin1	Pin1
Pin2	Pin2
Pin3	Pin3
Pin4	Pin4
Shell	Shell

I	Directive 2002/95/EC RoHS Compliant
	Directive 2002, 50, 20 Horis compilarit

_												
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF COMEC CORPORATION	ING BY HAND	Customer:				Tolerance Unless otherwise specified 0 PLC ± 0.30		₩	Scale:	Dim. in mm		
		Na	ame	Title	Approval Date	1 PLC ±0.20 2 PLC ±0.10 3 PLC ±0.05 ANGLES ±1'		Autodesk Inventor	Material: See Notes			
	SSE	ALTER CAD DRAWING					2012	Date	Name	IP67 USB Type	A E/E Adapte	י
	T OF I						Draw.	Sept. 27	Vincent Ke		•	
	NE SE						Appd.	Sept. 27	J. Chaudry	Receptacle (with Fl	ange) Assembly	Kit
	WAY NO NO NO NO NO NO NO NO NO NO NO NO NO						Norm			Nickel Plated Zinc	Die-Cast Version	
	DOT NOT ALT	С	1 x c	May/22/201	Vincent ke	D-old			Drawing No. 471/4405	. 4	DIN	
		Ь	1 x b	Mar/05/201	Vincent Ke			Drawing No.: 17K1A354		A3		
		а	original					Part No.: 17-210111		Sheet		
		Rev.	Changes	Date	Name				1/1			