

111-05423

HellermannTyton

Article Number: 111-05423

Description: High-Temp. Cable Tie, 15.35" Long, 50lb Tensile Strength, PA46, Brown, 1000/pkg



Base Data		
	Local Order Number	T50L1STNLM4
	Type	T50L
	Color	Brown (BN)
	Features and Benefits	• Cable ties made of PA46 material provide a greater resistance to high heat exposures than PA66 heat stabilized material. • Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
	Quantity Per	bag
	Product Description	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	High-Temp. Cable Tie, 15.35" Long, 50lb Tensile Strength, PA46, Brown, 1000/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	50.0lbs
	Minimum Tensile Strength (Metric)	225.0N
	Length L (Imperial)	15.35"
	Length L (Metric)	390.0mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Inside Serrated
	Width W (Imperial)	0.18"
	Width W (Metric)	4.7mm
	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	1.5mm

111-05423

HellermannTyton

Product Dimensions	Bundle Diameter Max. (Imperial)	4.3"
	Bundle Diameter Max. (Metric)	110.0mm
	Thickness T (Metric)	1.4mm
Material and Specifications		
	Material	Polyamide 4.6 (PA46)
	Material Shortcut	PA46
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +275°F (-40°C to +135°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987