



Article Number: 161-63503

Description: Helawrap, HWPAV030, 1-1/4" (30mm) Dia, PA6V0, Black,

100 ft/reel

| Base Data | | |
|-----------------------|---------------------------------|--|
| | Local Order Number | 161-63503 |
| | Туре | HWPAV030 |
| | Color | Black (BK) |
| | Features and Benefits | Designed for applications that demand high flame retardant materials Unique open design allows for easy branch-offs at any point along the harness Overwrap formation provides abrasion protection and accommodates multiple bundle configurations Flexible construction and design is well suited for applications that involve movement and vibration Easy-to-use installation tool makes assembly fast and easy |
| | Quantity Per | reel |
| | Product Description | The Helawrap cable management system is the flexible routing and protection solution for industrial, datacom and electrical applications. Helawrap easily wraps around cables with a "zipper-like" motion to protect against abrasion and mechanical stress caused by movement and bending. A handy application tool is included in every package for faster installations. |
| | Short Description | Helawrap, HWPAV030, 1-1/4" (30mm) Dia, PA6V0, Black, 100 ft/reel |
| Product Dimensions | | |
| | Length L (Imperial) | 100.0ft |
| | Length L (Metric) | 30.48m |
| | Reel Length (imperial) | 100.0ft |
| | Variant | Spiral Binding |
| | Bundle Diameter Min. (Imperial) | 1.14" |
| | Bundle Diameter Min. (Metric) | 29mm |
| | Bundle Diameter Max. (Imperial) | 1.26" |
| | Bundle Diameter Max. (Metric) | 32mm |
| | Diameter D (imperial) | 1.25" |
| | Diameter D (metric) | 30.0mm |
| | Nominal Diameter (Imperial) | 1-1/4" |
| | Nominal Diameter (Metric) | 30.0mm |

generated on: 4/28/2017

161-63503



| Product Dimensions | Wall Thickness WT (Imperial) | 0.050" |
|--------------------------------|------------------------------|----------------------------------|
| | Wall Thickness WT (Metric) | 1.30mm |
| | Pitch (imperial) | 0.94" |
| | Pitch (metric) | 23.88mm |
| Material and Specifications | | |
| | Material | Polyamide 6 V0 (PA6V0) |
| | Material Shortcut | PA6V0 |
| | Flammability | UL 94 V0 |
| | Halogenfree | Yes |
| | Operating Temperature | -40°F to +194°F (-40°C to +90°C) |
| | ROHS Compliant | Yes |
| | Certification/Specification | UL UL 1441 |
| | UL Recognized (US) | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 100ft |
| | Package Quantity (Metric) | 30.48m |
| | Customs Number(Schedule B) | 3926909987 |
| | Weight (imperial) | 9.83lbs |
| | Weight (Metric) | 4.46kg |

generated on: 4/28/2017