

	Date	SYM	REVISION RECORD	AUTH	DR.	CK.
	10/22/05	Α	ADDED "ROHS COMPLIANT"	T.B.	B.S.	
	5/02/08	В	ADDED NOTE	T.B.	B.S.	
1						

NOTE:

ORIENTATION OF SNAPS AND WIRES VARIES AND IS SHOWN FOR REFERENCE ONLY. RED WIRE TO POSITIVE CONTACT. BLACK WIRE TO NEGATIVE CONTACT.

ROHS COMPLIANT

N0.	PART NAME	MATERIAL	QTY.	Tolerance (Memory Protection Devices, Inc			
1	COVER	PVC COVER OVER FIBERBOARD	1	(Except as noted)	Memory Prote		ad, Farmingdale, New York 11735		
2	BLACK WIRE(-)	24 AWG, UL-1007, CSA TR-64, 300V, 80°C	1	decimal				Scale	Drawn By B.S.
3	RED WIRE (+)	24 AWG, UL-1007, CSA TR-64, 300V, 80°C	1	±.5 (.020)					
4	FEMALE SNAP	PHOSPHOR BRONZE, NICKLE PLATED, HEAVY DUTY	1						Approved By T.B.
5	MALE SNAP	BRASS NICKLE PLATED	1	Fractional	Title	9 VOLT BATTERY SNAP-I STYLE, HEAVY DUTY,			
			± .8 (.030)	6" WIRE LEADS					
				Angular	Date		Drawing Number		
				± 3°	5/02,	708 BS6I-HD			