



JKL LAMP NUMBER	VOLTS RATED	AMPS $\pm 10\%$	MSCP $\pm 25\%$	LUMENS $\pm 25\%$	AVERAGE LIFE HRS.	FILAMENT TYPE AND POSITION
1034	12.8	1.80	32.0	402.2	200	C-2R POSITION #2 = 2 FILAMENTS
	14.0	.59	3.0	37.7	5,000	C-2R POSITION #1 = 1 FILAMENT
1157	12.8	2.10	32.0	402.2	1,200	C-2R POSITION #2 = 2 FILAMENTS
	14.0	.59	3.0	37.7	3,000	C-2R POSITION #1 = 1 FILAMENT

METRIC DIMENSIONS ARE IN MILLIMETERS

TOLERANCE UNLESS OTHERWISE SPECIFIED

1 PL +/- 0.2

2 PL +/- 0.20

ANGLE +/- 0

THIRD ANGLE PROJECTION

JKL COMPONENTS CORPORATION

TITLE: **S-8 DOUBLE CONTACT INDEX BAYONET BASE LAMP**

DRAWN BY: L. WENGSTROM

APPV'D BY: QC

DATE: 5/18/01

DATE: 5/18/01

- CAD DRAWING -

MANUAL REVISIONS NOT PERMITTED

SIZE: **A**

FSCM NO.: **55335**

DRAWING NO.: **BAYONET DOUBLE CONTACT INDEX S-8**

SCALE: **NONE**

RELEASED DATE: **5/9/01**

REVISION DATE: **5/18/01**

REV. NO.: **A**

SHEET: **1 OF 1**

REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE
A	DIM. CHNG ON CONTACTS TO 6.48/7.08 RELEASED AS CAD	5/18/01 5/9/01