

VCO Product Specification

Model: VCO790-600T(Y) Rev: P5 Date: 10/17/2006

Customer: SIRENZA MICRODEVICES, INC.

Operating Temperature Range: (-40 ° to 70 ° C)

RoHS Compliant

To order models as RoHS Compliant add "Y" suffix to base model number.

Parameter	Min	Тур	Max	Units	Х	Remarks		
Frequency Range -	400		800	MHz	Х			
Tuning Voltage:								
400 MHz	0.5	2		Vdc	Х			
800 MHz		14	20	Vdc	Х			
Tuning Sensitivity:								
400 MHz	15	22	30	MHz/V	Х			
500 MHz	24	30	36	MHz/V	Х			
600 MHz	24	30	36	MHz/V	Х			
700 MHz	24	30	36	MHz/V	Х			
800 MHz	24	30	36	MHz/V	Х			
Output Power -	1.5	5.5	9.5	dBm	Х			
Output Phase Noise:								
1 kHz		-72	-66	dBc/Hz				
10 kHz		-102	-96	dBc/Hz				
100 kHz		-122	-116	dBc/Hz	Х			
Power Supply -	4.75	5	5.25	Volts				
Supply Current -		23	30	mA	Х			
Harmonic Suppression:								
2nd Harmonic		-5	-2.5	dBc	Х			
3rd Harmonic		-12	-6	dBc	Х			
Spurious (Non-Harmonic) -			-80	dBc				
Frequency Pushing - from 4.75 to 5.25 V		0.5	2	MHz p-p				
Frequency Pulling - into a 12 BB RL		2	5	MHz p-p				
Tuning Port Capacitance -		220		pF				
Output Impedance -		50		Ω				

Package Information

Package Type: T (0.5 x 0.5 x 0.156 inches)	Drawing Number:	60035
--	-----------------	-------

Comments

X Indicates parameter to be tested 100% in production

Performance tests and ratings for Sirenza Microdevices' products were performed internally by Sirenza and measured using specific computer systems and/or components and reflect the approximate performance of the the products as measured by those tests. Any difference in circuit implementation, test software, or test equipment may affect actual performance. The information provided herein is believed to be reliable at press time and Sirenza Microdevices assumes no responsibility for the use of this information. All such use shall be entirely at the user's own risk. Prices and specifications for Sirenza Microdevices' products are subject to change without notice. Buyers should consult Sirenza Microdevices' standard terms and conditions of sale for Sirenza's limited warranty with regard to its products. These products may be patented or include patented technology. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. Sirenza Microdevices does not authorize or warrant any product for use in life-support devices and/or systems.

Page 1 of 1