

 Date
 SYM
 REVISION RECORD
 AUTH
 DR. CK.

 10/22/05
 A
 ADDED "ROHS COMPLIANT"
 T.B.
 B.S.

 5/02/08
 B
 ADDED NOTE
 T.B.
 B.S.

NOTE:

ORIENTATION OF SNAPS AND WIRES VARIES AND IS SHOWN FOR REFERENCE ONLY. RED WIRE TO POSITIVE CONTACT. BLACK WIRE TO NEGATIVE CONTACT.

ROHS COMPLIANT

N0.	PART NAME	MATERIAL	QTY.	Tolerance		Mem	lemory Protection Devices, Inc		
1	COVER	PVC COVER OVER FIBERBOARD	1	(Except as noted)		200	200 Broad Hollow Road, Farmingdale, New York 11735		
2	BLACK WIRE(-)	24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C	1	decimal				Scale	Drawn By B.S.
3	RED WIRE (+)	24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C	1	5 (000)					·
4	FEMALE SNAP	BRASS, NICKLE PLATED	1	±.5 (.020)					Approved By T.B.
5	MALE SNAP	BRASS NICKLE PLATED	1	Fractional	Title	A MALE DARRED WALL A CONTRACT WINE LEADS			
				± .8 (.030)	9 VOLT BATTERY SNAP-I STYLE-6" WIRE LEADS				
				Angular	Date		Drawing Nu		
				± 3°	5/02,	/08 BS6I			