



PANEL THICKNESS	X
0.75-1.25	[.030-.049] 19.2 [.756]
1.25-2.0	[.049-.079] 19.4 [.764]
2.0-3.0	[.079-.118] 19.8 [.780]



SWITCH FUNCTION			
POS. 1	POS. 2	POS. 3	
DN	OFF	DN	
1a-1	DPEN	1-1b	



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
  3. TERMINAL NUMBERS FOR REF ONLY.
  4. RATING: 15A @ 125VAC OR 6A @ 250VAC
  5. MECHANICAL LIFE: 15,000 cycles
  6. ELECTRICAL LIFE: 10,000 cycles
  7. INSULATION RESISTANCE: >1000 Mega Ω
  8. CONTACT RESISTANCE: <20 Mega Ω
  9. DIELECTRIC STRENGTH: >1500 V 1 minute >3000 V between poles

**E-SWITCH®**

B	11662	REVISED PART DESCRIPTION	12/6/01	CJB
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE	R1966D BLK BLK B F
SCALE	1.5:1
DATE	2/22/96
DR	MM
DWG	M309301
REV	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED